

## SAFE- SLEEVE MSHA

Easy – to – install, textile MSHA-approved SAFE- SLEEVE is produced from polyester which is recyclable material.

In additional to hoses, SAFE- SLEEVE MSHA protects people near – by a breaking hose and meets the requirements of standards EN ISO 3457 and EN 12999.

The recommended temperature range is -40...- + 120°C. SAFE-SLEEVE MSHA is UV-protected and has a very low conductivity of electricity. Abrasion resistance of SAFE-SLEEVE MSHA is excellent.

Test reports are available on request.

Colour black with white printing.  
Own printing possible.

Length 50m/roll



<b>SAFE- SLEEVE MSHA product code</b>	<b>Inner diameter(mm) Tolerance +/- 0.5mm</b>
MSHA – RD17M	17
MSHA – RD23M	23
MSHA – RD27M	27
MSHA – RD30M	30
MSHA – RD36M	36
MSHA – RD39M	39
MSHA – RD46M	46
MSHA – RD55M	55
MSHA – RD62M	62
MSHA – RD78M	78
MSHA – RD109M	109
MSHA – RD125M	125

### GENTLE AUTOMATIC SOLUTION SDN BHD

No 36, Jalan Industri USJ1/13, Taman Perindustrian USJ 1, 47600 Subang Jaya, Selangor D.E, Malaysia

Tel : 603-80237743 / 8743

Fax : 03-80239743

[http : //www.gentle.com.my](http://www.gentle.com.my)

Email : [sales@gentle.com.my](mailto:sales@gentle.com.my)