

SAFE-SLEEVE

Easy – to – install, textile SAFE-SLEEVE is produced from polypropylene which is very hard- wearing and recyclable. In general, polypropylene endures acids and alkalis.

SAFE – SLEEVE protects people near – by a breaking hose and meets the requirements of EN 12999 and EN ISO 3457 standard . Its has excellent pressure resistance.

The recommended temperature range is -40..- +80°. SAFE –SLEEVE is UV-protected and has a very low conductivity of electricity. Abrasion resistance of SAFE- SLEEVE is excellent: when tested (standard SFS-EN ISO 12947-3)the mass of a competing sleeve was 10 times bigger than SAFE- SLEEVE's.

Colour black, NO printing
Length 50m/roll

SAFE- SLEEVE product code	Inner diameter(mm) Tolerance +/- 0.5mm
SL – RD 17	17
SL – RD 23	23
SL – RD 27	27
SL – RD 30	30
SL – RD 36	36
SL – RD 39	39
SL – RD 46	46
SL – RD 55	55
SL – RD 62	62
SL – RD 78	78
SL – RD 109	109
SL – RD 125	125

Aluminium rings for clamping the sleeve on the hose are also available!

GENTLE AUTOMATIC SOLUTION SDN BHD

No 36, Jalan Industri USJ1/13, Taman Perindustrian USJ 1, 47600 Subang Jaya, Selangor D.E, Malaysia

Tel : 603-80237743 / 8743

Fax : 03-80239743

[http : //www.gentle.com.my](http://www.gentle.com.my)

Email : sales@gentle.com.my