

Normally Closed Solid State Auto Switch Direct Mounting Style D-F9G/D-F9H



Grommet

Output signal turns on when no magnetic force is detected.



Caution

Precautions

Fix the auto switch with the existing screw installed on the auto switch body. The auto switch may be damaged if a screw other than the one supplied is used.

Auto Switch Specifications


PLC: Programmable Logic Controller

D-F9G, D-F9H (With indicator light)		
Auto switch model	D-F9G	D-F9H
Wiring type	3-wire	
Output type	NPN	PNP
Applicable load	IC circuit, Relay, PLC	
Power supply voltage	5, 12, 24 VDC (4.5 to 28 VDC)	
Current consumption	10 mA or less	
Load voltage	28 VDC or less	—
Load current	40 mA or less	80 mA or less
Internal voltage drop	1.5 V or less (0.8 V or less at 10 mA load current)	0.8 V or less
Leakage current	100 μ A or less at 24 VDC	
Indicator light	Red LED illuminates when detecting nothing.	
Standard	CE marking	


• Lead wires — Oilproof heavy-duty vinyl cord, ϕ 2.7, 0.15 mm², 3 cores (Brown, Black, Blue) 0.5 m
 Note 1) Refer to page 1272 for solid state auto switch common specifications.
 Note 2) Refer to page 1272 for lead wire lengths.

Auto Switch Internal Circuit

D-F9G



D-F9H



Mass

(g)

Auto switch model	D-F9G	D-F9H
Lead wire length (m)	0.5	7
	3	37
	5	61

Dimensions

(mm)

