2-Color Indicator Reed Auto Switch Tie-rod Mounting Type D-A59W

(€ 24

Grommet

The proper operating range can be determined by the color of the light. (Red \rightarrow Green \leftarrow Red)



Precautions

Do not drop or bump the auto switch while handling it as it may result in the auto switch breaking.

Auto Switch Specifications

	PLC: Programmable Logic Controller	
D-A59W (With indicator light)		
Auto switch model	D-A59W	
Applicable load	Relay, PLC	
Load voltage	24 VDC	
Load current range ⁽³⁾	5 to 40 mA	
Internal circuit*	У	
Contact protection circuit	Built-in	
Internal voltage drop	4 V or less	
Indicator light	Operating range Red LED illuminates. Proper operating range Green LED illuminates.	
Standard	CE/UKCA marking	

Oilproof Heavy-duty Lead Wire Specifications

Auto switch model		D-A59W
Sheath	Outside diameter [mm]	ø4
Insulator	Number of cores	2 cores (Brown/Blue)
	Outside diameter [mm]	ø1.22
Conductor	Effective area [mm ²]	0.3
	Strand diameter [mm]	ø0.08
Lædwirennimumbendhgradus(mm)(Referencevalues)		24

*Refer to the applicable internal circuit diagram (numbers q to u) on page 1587.

Note 1) Refer to page 1584 for reed auto switch common specifications. Note 2) Refer to page 1584 for lead wire lengths.

Note 3) Under 5 mA, the strength of the indicator light is poor. In some cases, visibility of the indicator light will not be possible where the output signal is less than 2.5 mA. However, there is no problem in terms of contact output, when an output signal exceeds 1 mA or more.

Weight

Auto switch model		D-A59W
Lead wire length	0.5 m (Nil)	25
	3 m (L)	80


Dimensions

(mm)

D-

waze.to/lr/hw28325k63

(q)



www.gentle.com.my

Gentle Automatic Solution Sdn Bhd

No.36, Jalan Industri USJ 1/13, Taman Perindustrian USJ 1, 47600 Subang Jaya, Selangor.