2-Color Indicator with Diagnostic Output Solid State Auto Switch: Band Mounting Type D-H7NF

Auto Switch Specifications

Refer to SMC website for the details of the products conforming to the international standards

PLC: Programmable Logic Controller

D-H7NF (With indicator light)			
Auto switch model	D-H7NF		
Wiring type	4-wire		
Outputtype	NPN		
Diagnostic output	Normal operation		
Applicable load	IC circuit, Relay, PLC		
Power voltage	5, 12, 24 VDC (4.5 to 28 VDC)		
Current consumption	10 mA or less		
Load voltage	28 VDC or less		
Load current	50 mA or less at the total amount of normal output and diagnostic output		
Internal voltage drop	1.5 V or less (0.8 V or less at each output 5 mA)		
Current leakage	100 μA or less at 24 VDC		
Indicator light	Operating rangeRed LED illuminates. Proper operating rangeGreen LED illuminates.		
Standard	CE/UKCA marking		

Oilproof Heavy-duty Lead Wire Specifications

<u> </u>	Olipidol ricavy daty Lead Wife Opecifications				
Auto switch model		D-H7NF			
Sheath	Outside diameter [mm]	ø3.4			
Insulator	Number of cores	4 cores (Brown/Blue/Black/Orange)			
	Outside diameter [mm]	ø0.98			
Conductor	Effective area [mm²]	0.2			
	Stranddiameter [mm]	ø0.08 id state auto switch common specifications.			
Minimumbendingradius(mm)(Referencevalues)		d wire lengths. 21			

Weight

Auto switch model		D-H7NF
Lead wire length	0.5 m (Nil)	13
	3 m (L)	56
	5 m (Z)	90

Grommet

Since the diagnostic output signal can be detected in the red display area, the difference of detecting position can be confirmed by the side of PLC (Programmable Logic Controller).




Dimensions


4.3 Smartigde 10.5 Most sensitive position

Diagnostic Output Operation

(mm)

The diagnostic output signal is output within the red display area (where indicator light is Red), and the diagnostic output becomes OFF when OUT the detecting position remains (Normaloutput) within the proper operating Lead wire (Black) range, (where indicator is Green). When the detecting position is not adjusted, the diagnostic output becomes





Gentle Automatic Solution Sdn Bhd



(g)